
















DATOS TÉCNICOS

Floor

Technical specifications Características técnicas	Standard Norma	Panama	Chroma	Memphis	Wicker
 Composition / Composición	-	75% Vinyl + 25% polyester + backing 100% vinyl	91% Vinyl + 9% polyester + backing 100% vinyl	75% Vinyl + 25% polyester + backing 100% vinyl	87% Vinyl + 13% polyester + backing 100% vinyl
 Weight / Peso (g/m²) (oz/sq ft)	ISO 8543:1998	2500 g/m ² +13% / -10% 8.5 oz/sq ft +13% / -10%	3500 g/m ² +13% / -10% 10.7 oz/sq ft +13% / -10%	3100 g/m ² +13% / -10% 10.2 oz/sq ft +13% / -10%	3500g/m ² +13% / -10% 10.8 oz/sq ft +13% / -10%
Weight / Peso (g/m²) (oz/sq ft) <small>Based on Acacia Floor Tiles / Lasetas autoportantes</small>	ISO 1715:1984	4500 g/m ² +13% / -10% 13.0 oz/sq ft +13% / -10%	4275 g/m ² +13% / -10% 14.0 oz/sq ft +13% / -10%	4300 g/m ² +13% / -10% 14.1 oz/sq ft +13% / -10%	4275 g/m ² +13% / -10% 14.0 oz/sq ft +13% / -10%
 Thickness / Espesor (mm.) (in)		2.25 mm 0.09 in	2.70 mm 0.11 in	2.30 mm 0.09 in	2.60 mm 0.10 in
Thickness / Espesor (mm.) (in) <small>Based on Acacia Floor Tiles / Lasetas autoportantes</small>		2.90 mm 0.11 in	3.35 mm 0.13 in	3.00 mm 0.12 in	3.30 mm 0.13 in
 Light Fastness / Solidez a la luz (Grey scale/Escala de grises: 1-5)	EN ISO 4892:2006 (exterior)	5/5 White/Blanco 4/5	5/5 White/Blanco 4/5	5/5 White/Blanco 4/5	5/5 White/Blanco 4/5
 Light Fastness / Solidez a la luz (Blue scale/Escala de azules: 1-8)	EN ISO 105B02:2001 (interior)	8/8 White/Blanco 7/8	8/8 White/Blanco 7/8	8/8 White/Blanco 7/8	8/8 White/Blanco 7/8
 Dimensional Stability % Estabilidad dimensional %	EN ISO 23999:2012	≤0.25%	≤0.25%	≤0.25%	≤0.25%
 Residual Indentation Huella residual	EN ISO 24343-1:2012	+0.10 mm +0.003 in	+0.30 mm +0.011 in	+0.10 mm +0.003 in	+0.10 mm +0.003 in
 Castor Chair Test Ensayo silla con ruedas.	EN 985:2002	Intensive use Uso intenso	Intensive use Uso intenso	Intensive use Uso intenso	Intensive use Uso intenso
 Sound Insulation / Aislamiento acústico	EN ISO 10140-3:2011	13 dB	14 dB	12 dB	14 dB
Sound Insulation / Aislamiento acústico <small>Based on Acacia Floor Tiles / Lasetas autoportantes</small>		14 dB	15 dB	13 dB	15 dB
 Thermal Resistance Resistencia térmica	EN 12647:2001	< 0.15 m ² K/W	< 0.15 m ² K/W	< 0.15 m ² K/W	< 0.15 m ² K/W
 Static Electricity Electricidad estática	EN 1815:1997	< 2 kV	< 2 kV	< 2 kV	< 2 kV
 Slip Resistance Resistencia al deslizamiento	EN 13893:2003 DIN 51130:2014	>0.4 R10	>0.4 R9	>0.35 R10	>0.4 R9
 Fire Classification Clasificación de fuego	EN 13501-1:2007 ASTM D2869 (2011)	BFS1 Pass	BFS1 Pass	BFS1 Pass	BFS1 Pass
Smoke density / Densidad de humos	ASTM E662-09	Pass	Pass	Pass	Pass
Volatiles emission Emisiones volátiles	Floorscore Certified	Floorscore Certified	Floorscore Certified	Floorscore Certified	Floorscore Certified
Antibacterial activity Comportamiento antibacteriano	ASTM E 2180-07(2012) ASTM G21-2013	Inhibition of bacterial growth Inhibe crecimiento bacterias Antifungal activity Actividad antifúngica	Inhibition of bacterial growth Inhibe crecimiento bacterias Antifungal activity Actividad antifúngica	Inhibition of bacterial growth Inhibe crecimiento bacterias Antifungal activity Actividad antifúngica	Inhibition of bacterial growth Inhibe crecimiento bacterias Antifungal activity Actividad antifúngica
 Roll Width / Ancho del rollo	-	200 cm 78.740 in	200 cm 78.740 in	200 cm 78.740 in	200 cm 78.740 in
 Roll Length / Largo del rollo	-	10 lm 32.81 ft 20 lm 65.62 ft	10 lm 32.81 ft 20 lm 65.62 ft	10 lm 32.81 ft 20 lm 65.62 ft	10 lm 32.81 ft 20 lm 65.62 ft
CE classification / Clasificación CE	EN 14861:2004	0338-CPR-2002	0338-CPR-2002	0338-CPR-2002	0338-CPR-2002
Use classification / Clasificación de uso	EN 1307:2014	Heavy Commercial / Comercial de alto tráfico	Heavy Commercial / Comercial de alto tráfico	Heavy Commercial / Comercial de alto tráfico	Heavy Commercial / Comercial de alto tráfico