

DATOS TÉCNICOS

Soundless

	Standard	Panama	Chroma	Memphis	Wicker	Polo
Composición Composition	-	75% Vinyl + 25% polyester Backing 94% vinyl + Felt PES 4%	91% Vinyl + 9% polyester Backing 94% vinyl + Felt PES 4%	75% Vinyl + 25% polyester Backing 94% vinyl + Felt PES 4%	87% Vinyl + 13% polyester Backing 94% vinyl + Felt PES 4%	90% Vinyl + 10% polyester Backing 94% vinyl + Felt PES 4%
Peso (g/m²) Weight (g/m²) Guidance data	ISO 8543:1998	7250 g/m² +15% / -10%	7100 g/m² +15% / -10%	7220 g/m² +15% / -10%	6710 g/m² +15% / -10%	7667 g/m² +15% / -10%
Grosor (mm.) Thickness (mm.) Guidance data	ISO 1745:1998	5,95 mm	5,96 mm	6,4 mm	5,86 mm	6,09 mm
Solidez a la luz Light Fastness	EN ISO 4892:2006 (Exterior)	5/5 White 4/5	5/5 White 4/5	5/5 White 4/5	5/5 White 4/5	5/5 White 4/5
Solidez a la luz Light Fastness	EN ISO 10580:2001 (Interior)	6/6 White 7/8	6/6 White 7/8	6/6	6/6 White 7/8	6/6 White 7/8
Prueba Carbor Chair Carbor Chair Test	EN 950:2002	Uso Intensivo Intensive Use	Uso Intensivo Intensive Use	Uso Intensivo Intensive Use	Uso Intensivo Intensive Use	Uso Intensivo Intensive Use
Static Electricity Electricidad Estática	EN 1816:1997	< 2 kV	< 2 kV	< 2 kV	< 2 kV	< 2 kV
Thermal Resistance Resistencia Térmica	EN 12667:2004	< 0,16 m² K/W	< 0,16 m² K/W	< 0,16 m² K/W	< 0,16 m² K/W	< 0,16 m² K/W
Dimensional Stability Estabilidad dimensional	EN ISO 23999:2002	≤ 0,25	≤ 0,25	≤ 0,25	≤ 0,25	≤ 0,25
Residual Indentation Sangría residual	EN ISO 14243 1:2002	0,60	0,60	0,60	0,60	0,60
Aislamiento acústico Sound Insulation	EN ISO 10140-3:2001	20 dB	20 dB	20 dB	19 dB	20 dB
Resistencia al deslizamiento Slip Resistance	EN 15645:2003	> 0,4	> 0,4	> 0,4	> 0,4	> 0,4
Resistencia al deslizamiento Slip Resistance	DIN 51130:2014	R10	R9	R10	R10	R10
Resistencia al deslizamiento Slip Resistance	ASTM C1028-95 Static Coefficient	Wet 0,45 Dry 0,75	Wet 0,59 Dry 0,72	Wet 0,79 Dry 0,86	Wet 0,62 Dry 0,7	Wet 0,75 Dry 0,78
Clasificación al fuego Fire Classification	EN 13501-1:2007	BFs1	BFs1	BFs1	BFs1	BFs1
Clasificación de uso Use Classification	EN 1307:2014	Comercial intenso Heavy Commercial	Comercial intenso Heavy Commercial	Comercial intenso Heavy Commercial	Comercial intenso Heavy Commercial	Comercial intenso Heavy Commercial
Dimensión loseta Tile Dimensions	Cuadrado Square 300x300 mm					