








DATOS TÉCNICOS

Wall

Technical specifications Especificaciones técnicas	Standard Norma	Memphis	Panama	Ethereal
 Composition Composición	-	80% PVC + 20% PES PP Backing	80% PVC + 20% PES PP Backing	80% PVC + 20% PES PP Backing
 Weight (g/m²) Peso (g/m ²)	UNE EN 12127	415±10%	437±10%	437±10%
 Thickness (mm.) Espesor (mm.)	UNE EN ISO 5084:1997	0.65±10%	0.59±10%	0.59±10%
 Light Fastness (Blue scale: 1-8) Solidez a la luz (Escala de azules: 1-8)	UNE EN ISO 105 B02-2002	≥ 7/8	≥ 7/8	≥ 7/8
Fire Classification Clasificación al fuego	EN 13501-1:2007	Bs2d0	Bs2d0	Bs2d0
 Roll Width Ancho del rollo	-	100 cm	100 cm	100 cm
 Roll Length Largo del rollo	-	9 ml	9 ml	9 ml
 Abrasion resistance Resistencia a la abrasión	UNE EN ISO 12947	>100000 cycles	>100000 cycles	>100000 cycles

All specifications are based on average values and may deviate. The values are for guidance and are not contractual. Subject to technical modifications. The straight weft is not an inherent condition. Weaving technology features colour effects because of light, making it an exclusive and unique product. Also, bicolour yarns create a randomly harmonious effect. These effects are no ground for claims.

Todas las especificaciones están basadas en promedios y pueden variar. Los valores son una guía y no son contractuales. Están sujetos a modificaciones técnicas. La trama recta no es una condición inherente. La forma en que está tejido provoca efectos de color a causa de la luz, convirtiéndolo en un producto único y exclusivo. Los tejidos bicolor crean un efecto armónico aleatorio. Estos efectos no son motivo de reclamación.